







Super-Mat 2

Customs tariff number:

57032999

Product details:

- » Made of Econyl® regenerated nylon which is made entirely from ocean and landfill waste
- » Dual performance scrape and wipe
- » Skid resistant rubber back
- » Light- and colour resistant
- » PVC-free
- » Suitable for underfloor heating
- » 5 year Manufacturers Guarantee*
- » 11 year warranty against significant colour loss
- » Made in Europe

Burning behaviour: EN 13501-1 / Cfl-s1

Static electrical propensity: EN 14041 Antistatic

Slip resistance: NFSI High-Traction

Total mat weight: 3.10 kg/sqm

Overall height: approx. 10 mm

Dirt absorption: 950 g/sqm Moisture absorption: 3 - 4 l/sqm

» Heavy traffic areas **Application areas:**

» Busy entrances

Standard widths with borders: 85 cm, 115 cm and 150 cm

Standard widths

without borders:

3 cm smaller than for mats with borders

1234

(e.g. 82 cm)

Standard lengths: all lengths up to 700 cm

Colouration: Solution dyed

Pile:

100 % Econyl® regenerated nylon

approx. 9 mm

Pile height: Pile weight:

Rubber thickness:

Border thickness:

Rubber weight:

Border width:

without substrate: 800 g/sqm

100 % Nitrile rubber

with substrate: 900 g/sqm

Backing:

Available with kleeted or smooth backing 1.80 mm

2.20 kg/sqm

20 mm

Available with or without borders 2.80 mm

Cleaning: » Washable up to 60 °C

» Tumble dry up to 60 $^{\circ}\text{C}$

Colours:



